

Product name	2LV		2L				3L	3L 120
Product code	UP-2LV-22	UP-2LV-29	UPMOD-2L-22	UPMOD-2L-29	UP-2L-22	UP-2L-29	UP-3L	UPMOD-3L-120
SPECIFICATIONS								
Height range	21.6"-47.9"							
Width range	41.3"-72.8"		N/A		46"-77.3"		Main Frame: 46"-77" Extension Leg: 42"-72"	24" Depth: 36"-54" 30" Depth: 36"-42"
Depth of foot	21.65"	29.5"	21.65"	29.5"	21.65"	29.5"	21.65"	
Depth of bracket	19.7"		21.65"					
Assembly time*	15-25 min						20-30 min	
Travel speed	1.6" per second							
Volume	39 Db.							
Weight capacity	220 lbs		250 lbs		300 lbs		420 lbs	400 lbs
Motors	2 (1 per leg)						3 (1 per leg)	
Max operational power draw	180W		280W					
Standby power draw	<0.1W							
Tabletop size range	22"d x 44"w 28"d x 84"w	29"d x 44"w 36"d x 84"w	22"d x 30"w 28"d x 47"w	29"d x 30"w 36"d x 47"w	22"d x 48"w 28"d x 96"w	29"d x 48"w 48"d x 96"w	Main Frame: 48"-96" Extension Leg: 42"-96"	24" Depth: 36"-54" 30" Depth: 36"-42"
Power cord length	1.8m (71")							
FEATURES								
Frame finish options	Silver, black				Silver, black, white			Silver, black
Built-in gyro-sensor anti-collision system	Yes							
Adjustable sensitivity for anti-collision system	Yes							
Battery option	No		Yes				No	
Casters available	Yes						No	
Digital height adjustment handset	Digital display – 4 presets							
Settable min/max heights	Yes							
One touch adjustment to pre-sets	Yes							
Parallel connectivity	No		Yes					
Changeable inch or cm height display	Yes							
Certifications	CSA/UL Listed CSA22.2 No. 203 CSA22.2 No. 14 CSA22.2 No. 68-09 BIFMA G1 BIFMA X5.5 BIFMA e3 Level 2 GREENGUARD Gold®							

* Frame assembly only – does not include table top attachment. Tabletop attachment adds 5-10 min.